



## FZW Fizeau Laser Wavemeter



The MOGLabs FZW Fizeau Laser Wavemeter is a precision compact self-contained wavemeter: *no host computer required.*

It measures from 400 to 1100nm with absolute accuracy better than 600MHz ( $3\sigma$ ). On-unit display, ethernet and USB connectivity, and PID locking, are standard. Time-series measurements at up to 500 measurements per second can be plotted on the display or on a host computer. The device is easily integrated with common lab data acquisition systems using simple text commands, and wrappers for LabVIEW, python and MATLAB.

Matching fibre switches are available, with 4 and 8 input ports, and 4 or 8 analogue outputs with PID to wavelength-stabilise up to 8 lasers.

### Features

- 600 MHz ( $3\sigma$ ) absolute accuracy, 400 to 1100nm (measurement range 350 to 1120nm)
- Self-contained with colour display
- Solid fused silica etalons
- 500 measurements per second
- Built-in PID feedback with analogue output
- Ethernet and USB standard

### Options

- FC/PC or FC/APC input available
- 4x1 and 8x1 fibre switches available (FC/APC only)

# Fizeau Wavemeter

## Specifications FZW600

### Wavelength/frequency

Wavelength range	350nm – 1120nm
Units	nm (vac), nm (air; NTP), THz, cm <sup>-1</sup>
Input power requirement	10nW @ 10 meas/sec; 500nW at 350 meas/sec (550nm)
Accuracy	600 MHz (3 $\sigma$ ) @ 400nm – 1100nm; typically 200MHz
Resolution	10 MHz (full speed); 1 MHz (100-sample average)
Exposure	100 $\mu$ s to 1 s
Measurement rate (>500 $\mu$ W)	500 /s (wide mode) 150 /s (fine mode)
Fizeau interferometers	4; smallest FSR = 7.5GHz
Calibration	Generally not required. Use stabilised HeNe or other well-known laser source, e.g. at 12-month intervals.
Warm-up time	Stated accuracy within 10 minutes

### Electronics

Display	Built-in 320x240 colour TFT LCD
PID feedback	12-bit DAC output, 0.5mV resolution
Power	+5V 600mA via USB or separate DC jack
On/off	Rocker switch on rear

### Communications

Ethernet	10/100 TP RJ45
USB	USB2.0, plug type USB-B (also used for power)
SPI	Internal; for OEM implementations

### Inputs/outputs

Optical input	FC/PC or FC/APC, singlemode
Multiplexer	FC/APC 4x1 or 8x1 fibre switch with 4 or 8 analogue outputs with PID
SMA DAC out	12-bit output, $\pm$ 2.5V, 0.5mV resolution
Power (alternate to USB power)	DC jack, + on centre 2.5mm pin

### Dimensions

Dimensions	120mm x 146mm x 81mm (DxWxH); 0.7kg
Dimensions with fibre switch	120mm x 146mm x 131mm (DxWxH); 1.35kg