



PDA030 Amplified photodetector



The MOGLabs PDA030 is an amplified silicon photodetector designed for Pound-Drever-Hall optical cavity locking. It provides high bandwidth, high quantum efficiency and low noise in a convenient mechanical enclosure with standard connectors.

The 50 Ω impedance signal is provided via an *isolated* BNC connector that helps eliminate ground loops. Power, for example from the MOGLabs FSC fast servo controller, is easily provided via Thorlabs-compatible M8 connector and standard industry M8 sensor cable. Optical tubes, filters and lenses are easily mounted using the standard SM1 threaded ring.

Features

- Internal transimpedance amplifier 7.5 kV/A
- High bandwidth DC to 30 MHz (Si)
- Low noise NEP 2 pW/ $\sqrt{\text{Hz}}$ at 1 MHz
- Wide spectral response 300 – 1060 nm
- High quantum efficiency 0.64 at 900 nm
- Isolated BNC connector to avoid ground loops
- Standard M8 power connector ± 7 to ± 15 v
- SM1 (1.035"-40) internal thread optical tube mount

Applications

- PDH laser frequency stabilisation
- Intensity noise eating

Specifications

Signal

Bandwidth (fast output)	Si DC – 30 MHz (-3 dB); InGaAs DC – 20MHz (-3dB)
Noise equivalent power	2 pW/ $\sqrt{\text{Hz}}$ at 1MHz, 3 pW/ $\sqrt{\text{Hz}}$ at 10MHz
Active area	Φ 1.2mm (1.1 mm ² area)
Sensor	Silicon Hamamatsu S5971 (option: S5972, S5973)
Quantum efficiency	Peak 0.64 at 900nm; see response curve below
Gain	7500 V/A

Mechanical

Power	± 7 to ± 15 V, 100 mA, M8 connector
Dimensions	43x53x19mm (W x H x D) body; 43x65x22 inc connectors and SM1 ring
Mounting	3 x M4/8-32 tapped holes
Signal connector	Isolated BNC 50 Ω impedance
Optics mount	SM1 (1.035"-40) thread, internal

